



E&E LIGHTING
AUSTRALIA

CODE: EXBOXL

LED CLASSIC BOX EXIT BODY ONLY - WALL / CEILING DIFFUSER

PRODUCT RANGE

CODE	DESCRIPTION	Carton Qty
EXBOXL	LED Classic Box Exit Body Only	5 pieces
DBOXW	Wall Diffuser to suit EXBOXL	5 pieces
DBOXC	Ceiling Diffuser to suit EXBOXL	5 pieces

ORDERING INFORMATION

PRODUCT	WEIGHT	DIMENSION (L X W X H)
Body Only	0.9kg (unit) - 4.5kg (box)	385mm x 100mm x 155mm
Wall Diffuser	0.5kg (unit) - 2.5kg (box)	385mm x 120mm x 155mm
Ceiling Diffuser	1.3kg (unit) - 6.5kg (box)	385mm x 150mm x 218mm

LED Classic Box Exit Body Only



Wall Diffuser



Ceiling Diffuser



OPERATIONAL INFORMATION

TECHNICAL SPECIFICATIONS

Operating Mode	Switch Maintained
Voltage (V); Frequency (Hz)	220-260V; 50Hz
Operating Temperature	1° - 45° C
IP Rating	IP20
Wiring	Large Terminal Block
Mounting Type	Wall or Ceiling Surface Mount
Testing System	Manual Test Switch
Construction	Polycarbonate Body and Diffuser
Classification	C0 D6.3 C90 D4 (Wall) C0 D10 C90 D8 (Ceiling)
Standards	AS/NZ 2293 AS/NZS 60598.1 EMC

BATTERY AND LEDS

Battery	High-Temp LiFePO4 Lithium Battery
Power Consumption	3W
Charging Method	3 Stage Intelligence
Charging Time	16 Hours
Lens	LED Lamp Rated 50,000 hours
Viewing Distance	24 Metres

REPLACEMENT PART

PART NUMBER	DESCRIPTION
BBOXL	LiFePO4 Lithium Battery, 3.2V 3200mAh

SPACING TABLE AND MOUNTING HEIGHT

CLASSIFICATION	2.1m	2.4m	2.7m	3m	3.3m	3.6m	4m	4.5m	5m
D4	7.1	7.2	7.3	7.3	7.2	7.1	6.9	0.0	0.0
D6.3	8.5	8.8	8.9	9.1	9.1	9.2	9.1	9.0	8.7
D8	9.4	9.7	9.9	10.1	10.2	10.3	10.3	10.3	10.1
D10	10.2	10.5	10.8	11.0	11.2	11.4	11.5	11.5	11.5



0487 248 481



sales@eelighting.com.au



eelighting.com.au