



E&E LIGHTING  
AUSTRALIA

# CODE: EXWAYBOX LED BOX EXIT BODY ONLY - WALL / CEILING DIFFUSER

## PRODUCT RANGE

CODE	DESCRIPTION	Carton Qty
EXWAYBOX	LED Box Exit Body Only	6 pieces
DWAYBOXW	Wall Diffuser to suit EXWAYBOX	6 pieces
DWAYBOXC	Ceiling Diffuser to suit EXWAYBOX	4 pieces

## ORDERING INFORMATION

PRODUCT	WEIGHT	DIMENSION (L X W X H)
Body Only	0.9kg (unit) - 4.8kg (box)	380mm x 65mm x 160mm
Wall Diffuser	0.5kg (unit) - 3.0kg (box)	380mm x 89mm x 160mm
Ceiling Diffuser	1.0kg (unit) - 4.0kg (box)	380mm x 160mm x 206mm

LED Box Exit Body Only



Wall Diffuser



Ceiling Diffuser



## OPERATIONAL INFORMATION

### TECHNICAL SPECIFICATIONS

Operating Mode	Switch Maintained
Voltage (V); Frequency (Hz)	220-260V; 50Hz
Operating Temperature	1° - 45° C
IP Rating	IP20
Wiring	Large Terminal Block
Mounting Type	Wall or Ceiling Surface Mount
Testing System	Manual Test Switch
Construction	Polycarbonate Body and Diffuser
Classification	C0 D4 C90 D2.5 (Wall) C0 D8 C90 D6.3 (Ceiling)
Standards	AS/NZ 2293 AS/NZS 60598.1 EMC

### BATTERY AND LEDS

Battery	High-Temp LiFePO4 Lithium Battery
Power Consumption	4W
Charging Method	3 Stage Intelligence
Charging Time	16 Hours
Lens	LED Lamp Rated 50,000 hours
Viewing Distance	24 Metres

### REPLACEMENT PART

PART NUMBER	DESCRIPTION
BWAYBOX	LiFePO4 Lithium Battery, 3.2V 1500mAh

### SPACING TABLE AND MOUNTING HEIGHT

CLASSIFICATION	2.1m	2.4m	2.7m	3m	3.3m	3.6m	4m	4.5m	5m
D4	7.1	7.2	7.3	7.3	7.2	7.1	6.9	0.0	0.0
D8	9.4	9.7	9.9	10.1	10.2	10.3	10.3	10.3	10.1
D2.5	5.8	5.8	5.7	5.6	5.3	0.0	0.0	0.0	0.0
D6.3	8.5	8.8	8.9	9.1	9.1	9.2	9.1	9.0	8.7



0487 248 481



sales@eelightning.com.au



eelightning.com.au