

PRODUCT RANGE

CODE	DESCRIPTION
EMLITEL	3W LED Recessed Emergency Luminaire
EMLITELBK	3W LED Recessed Emergency Luminaire - Black Finish

ORDERING INFORMATION

Carton Qty	10 pieces
Weight	0.6kg (unit) - 6.0kg (box)
Dimension (L x W x H)	228mm x 43mm x 27mm - Control Pack; 84mm(S), 145mm(L) - Head Diameter
Ceiling Hole Cut Out	70mm(S), 75-135mm(L)



White Finish



Black Finish

OPERATIONAL INFORMATION

TECHNICAL SPECIFICATIONS

Operating Mode	Non-Maintained
Voltage (V); Frequency (Hz)	220-260V; 50Hz
Operating Temperature	1° - 45° C
IP Rating	IP20
Wiring	Flex and Plug
Mounting Type	Recessed Mounted
Testing System	Manual Test Switch
Construction	Polycarbonate
Classification	C0 D40 C90 D40
Standards	AS/NZ 2293 AS/NZS 60598.1 EMC

BATTERY AND LEDS

Battery	High-Temp LiFePO4 Lithium Battery
Power Consumption	3W
Charging Method	3 Stage Intelligence
Charging Time	16 Hours
Lens	LED Lamp Rated 50,000 hours

REPLACEMENT PART

PART NUMBER	DESCRIPTION
BLITEL	LiFePO4 Lithium Battery, 3.2V 3200mAh

SPACING TABLE AND MOUNTING HEIGHT

CLASSIFICATION	2.1m	2.4m	2.7m	3m	3.3m	3.6m	4m	4.5m	5m
D40	11.5	13.2	14.8	16.5	18.1	19.5	20.1	20.7	21.2

