

# CODE: EMLITELSM

## 3W LED SURFACE MOUNT EMERGENCY LUMINAIRE

\*Cylinder format available

### PRODUCT RANGE

CODE	DESCRIPTION
EMLITELSM	3W LED Surface Mount Emergency Luminaire
EMLITELSMBK	3W LED Surface Mount Emergency Luminaire - Black Finish
EMLITELSMC	3W LED Surface Mount Cylinder Emergency Luminaire
EMLITELSMCBK	3W LED Surface Mount Cylinder Emergency Luminaire - Black Finish



White Finish

### ORDERING INFORMATION

Carton Qty	10 pieces
Weight	1.2kg (unit) - 12.0kg (box) 1.5kg (unit) - 15.0kg (box) - Cylinder format
Dimension (L x W x H)	270mm x 190mm x 55 mm 128mm x 252mm - Cylinder format



Black Finish

### OPERATIONAL INFORMATION

#### TECHNICAL SPECIFICATIONS

Operating Mode	Non-Maintained
Voltage (V); Frequency (Hz)	220-260V; 50Hz
Operating Temperature	1° - 45° C
IP Rating	IP20
Wiring	Large Terminal Block
Mounting Type	Surface Mounted
Testing System	Manual Test Switch
Construction	Powder Coated Metal Box
Classification	C0 D40 C90 D40
Standards	AS/NZ 2293 AS/NZS 60598.1 EMC

#### BATTERY AND LEDS

Battery	High-Temp LiFePO4 Lithium Battery
Power Consumption	3W
Charging Method	3 Stage Intelligence
Charging Time	16 Hours
Lens	LED Lamp Rated 50,000 Hours
Colour Temperature	5000K

#### REPLACEMENT PART

PART NUMBER	DESCRIPTION
BLITEL	LiFePO4 Lithium Battery, 3.2V 3200mAh

#### SPACING TABLE AND MOUNTING HEIGHT

CLASSIFICATION	2.1m	2.4m	2.7m	3m	3.3m	3.6m	4m	4.5m	5m
D40	11.5	13.2	14.8	16.5	18.1	19.5	20.1	20.7	21.2

