

PRODUCT RANGE

CODE	DESCRIPTION
EXBLADEL	3W LED Recessed Blade Exit
EXBLADEL BK	3W LED Recessed Blade Exit - Black Finish

ORDERING INFORMATION

Carton Qty	5 pieces
Weight	1.3kg (unit) - 13.0kg (box)
Dimension (L x W x H)	365mm x 95mm x 210mm (Overall) 365mm x 95mm x 160mm (Recessed)



OPERATIONAL INFORMATION

TECHNICAL SPECIFICATIONS

Operating Mode	Maintained
Voltage (V); Frequency (Hz)	220-260V; 50Hz
Operating Temperature	1° - 45° C
IP Rating	IP20
Wiring	Flex and Plug
Mounting Type	Recessed
Testing System	Manual Test Switch
Construction	Polycarbonate Body and Diffuser, Acrylic Lens
Classification	C0 D10 C90 C12.5
Standards	AS/NZ 2293 AS/NZS 60598.1 EMC

BATTERY AND LEDS

Battery	High-Temp LiFePo4 Lithium Battery
Power Consumption	3W
Charging Method	3 Stage Intelligence
Charging Time	16 Hours
Lens	LED Rated 50,000 Hours
Viewing Distance	24 Metres

REPLACEMENT PART

PART NUMBER	DESCRIPTION
BBLADEL	LiFePO4 Lithium Battery; 3.2V 3500mAh
PBLADEL	Adaptor plate 500mm x 150mm to suit EXBLADEL

SPACING TABLE AND MOUNTING HEIGHT

CLASSIFICATION	2.1m	2.4m	2.7m	3m	3.3m	3.6m	4m	4.5m	5m
D10	5.2	5.1	5.0	4.7	0.0	0.0	0.0	N/A	N/A
C12.5	4.5	4.6	4.6	4.5	4.4	0.0	0.0	0.0	0.0

