

CODE: EXBLADELSM

3W LED SURFACE MOUNT

BLADE EXIT

PRODUCT RANGE

CODE	DESCRIPTION
EXBLADELSM	3W LED Surface Mount Blade Exit
EXBLADELSMBK	3W LED Surface Mount Blade Exit - Black Finish

ORDERING INFORMATION

Carton Qty	5 pieces
Weight	1.4kg (unit) - 14.0kg (box)
Dimension (L x W x H)	365mm x 95mm x 220mm



White finish



Black finish

OPERATIONAL INFORMATION

TECHNICAL SPECIFICATIONS

Operating Mode	Maintained
Voltage (V); Frequency (Hz)	220-260V; 50Hz
Operating Temperature	1° - 45° C
IP Rating	IP20
Wiring	Large Terminal Block
Mounting Type	Wall or Ceiling Surface Mount
Testing System	Manual Test Switch
Construction	Polycarbonate Body, Acrylic Diffuser
Classification	C0 D10 C90 C12.5
Standards	AS/NZ 2293 AS/NZS 60598.1 EMC

BATTERY AND LEDS

Battery	High-Temp LiFePo4 Lithium Battery
Power Consumption	3W
Charging Method	3 Stage Intelligence
Charging Time	16 Hours
Lens	LED Lamp Rated at 50,000 Hours
Viewing Distance	24 Metres

REPLACEMENT PART

PART NUMBER	DESCRIPTION
BBLADELSM	LiFePO4 Lithium Battery; 3.2V 3500mAh

SPACING TABLE AND MOUNTING HEIGHT

CLASSIFICATION	2.1m	2.4m	2.7m	3m	3.3m	3.6m	4m	4.5m	5m
D10	5.2	5.1	5.0	4.7	0.0	0.0	0.0	N/A	N/A
C12.5	4.5	4.6	4.6	4.5	4.4	0.0	0.0	0.0	0.0

