

# CODE: EXBOXWPL

## 3W LED WALL MOUNT WEATHERPROOF MAINTAINED EXIT

\*4hr Duration format available

### PRODUCT RANGE

CODE	DESCRIPTION
EXBOXWPL	3W LED Wall Mount Weatherproof Maintained Exit - <b>Running Man No Arrow</b>
EXBOXWPLAR	3W LED Wall Mount Weatherproof Maintained Exit - <b>Running Man Arrow Right</b>
EXBOXWPLAL	3W LED Wall Mount Weatherproof Maintained Exit - <b>Running Man Arrow Left</b>
EXBOXWPLOPAL	3W LED Wall Mount Weatherproof Maintained Exit - <b>Opal Diffuser</b>

EXIT WITH +4HR DURATION

EXBOXWPL4H



### ORDERING INFORMATION

Carton Qty	5 pieces
Weight	2.2kg (unit) - 17.6kg (box)
Dimension (L x W x H)	380mm x 130mm x 190mm

### OPERATIONAL INFORMATION

#### TECHNICAL SPECIFICATIONS

Operating Mode	Switch Maintained
Voltage (V); Frequency (Hz)	220-260V; 50Hz
Operating Temperature	1° - 45 °C
IP Rating	IP67
Wiring	Large Terminal Block
Mounting Type	Wall Mount
Testing System	Manual Test Switch
Construction	ABS Body and Diffuser
Classification	C0 C2.5 C90 C2.5
Standards	AS/NZ 2293 AS/NZS 60598.1 EMC

#### BATTERY AND LEDS

Battery	High-Temp LiFePO4 Lithium Battery
Power Consumption	3W
Charging Method	3 Stage Intelligence
Charging Time	16 Hours
Lens	LED Lamp Rated at 50,000 Hours
Viewing Distance	24 Metres

#### REPLACEMENT PART

PART NUMBER	DESCRIPTION
BBOXWPL	LiFePO4 Lithium Battery; 3.2V 3200mAh
BBOXWPL4H	LiFePO4 Lithium Battery; 3.2V 3200mAh

#### SPACING TABLE AND MOUNTING HEIGHT

CLASSIFICATION	2.1m	2.4m	2.7m	3m	3.3m	3.6m	4m	4.5m	5m
C2.5	4.5	4.6	4.6	4.5	4.4	0.0 <sup>4</sup>	0.0 <sup>4</sup>	0.0 <sup>4</sup>	N/A

