

CODE: EXBOXWPLOPAL 3W LED WALL MOUNT WEATHERPROOF MAINTAINED EXIT

PRODUCT RANGE

PRODUCT CODE	DESCRIPTION
EXBOXWPLOPAL	33W LED Wall Mount Weatherproof Maintained Exit - Opal Diffuser

ORDERING INFORMATION

Carton Qty	5 pieces
Weight	2.2kg (unit) - 17.6kg (box)
Dimension (L x W x H)	380mm x 130mm x 190mm



OPERATIONAL INFORMATION

TECHNICAL SPECIFICATIONS

Operating Mode	Switch Maintained
Voltage (V); Frequency (Hz)	220-260V; 50Hz
Operating Temperature	1° - 45° C
IP Rating	IP67
Wiring	Large Terminal Block
Mounting Type	Surface Mounted
Testing System	Manual Test Switch
Construction	Polycarbonate Body and Diffuser
Classification	C0 D32 C90 D32
Standards	AS/NZ 2293 AS/NZS 60598.1 EMC

BATTERY AND LEDS

Battery	High-Temp LiFePO4 Lithium Battery
Power Consumption	3W
Charging Method	3 Stage Intelligence
Charging Time	16 Hours
Lens	LED Lamp Rated 50,000 hours
Colour Temperature	5000 K

REPLACEMENT PART

PART NUMBER	DESCRIPTION
BBOXWPL	LiFePO4 Lithium Battery. 3.2V 3500mAh

SPACING TABLE AND MOUNTING HEIGHT

CLASSIFICATION	2.1m	2.4m	2.7m	3m	3.3m	3.6m	4m	4.5m	5m	6m	7m	8m	9m	10m	15m
D32	11.5	13.2	14.8	16.5	17.6	18.0	18.5	19.0	19.5	20.1	20.5	20.7	20.6	20.3	0.0 ⁴

NOTE: Care should be taken when spacing luminaires at the distances indicated by the shaded regions to ensure that conformance to Clause 4.3 of AS/NZS 2293.1 is maintained (e.g. maximum 500 m2 per emergency luminaire).

