

# CODE: EXBOXWPLRB

## 3W LED WALL MOUNT WEATHERPROOF MAINTAINED FREEZER EXIT

- IP67

### PRODUCT RANGE

CODE	DESCRIPTION
EXBOXWPLRB	3W LED Wall Mount Weatherproof Maintained Freezer Exit - <b>Running Man No Arrow Remote Box</b>
EXBOXWPLARRB	3W LED Wall Mount Weatherproof Maintained Freezer Exit - <b>Running Man Right Arrow Remote Box</b>
EXBOXWPLALRB	3W LED Wall Mount Weatherproof Maintained Freezer Exit - <b>Running Man Left Arrow Remote Box</b>
EXBOXWPLOPALRB	3W LED Wall Mount Weatherproof Maintained Freezer Exit - <b>Opal Diffuser Remote Box</b>
EXIT WITH +4HR DURATION	
EXBOXWPL4H	



### ORDERING INFORMATION

Carton Qty	4 pieces
Weight	4.4kg (unit) - 17.6kg (box)
Dimension (L x W x H)	380mm x 130mm x 190mm

### OPERATIONAL INFORMATION

#### TECHNICAL SPECIFICATIONS

Operating Mode	Switch Maintained
Voltage (V); Frequency (Hz)	220-260V; 50Hz
Operating Temperature	-25° - 45° C
IP Rating	IP67
Wiring	Large Terminal Block
Mounting Type	Wall Mount
Testing System	Manual Test Switch
Construction	Polycarbonate Body and Diffuser
Classification	C0 C2.5 C90 C2.5
Standards	AS/NZ 2293 AS/NZS 60598.1 EMC

#### BATTERY AND LEDS

Battery	High-Temp LiFePO4 Lithium Battery
Power Consumption	3W
Charging Method	3 Stage Intelligence
Charging Time	16 Hours
Lens	LED Lamp Rated 50,000 hours
Viewing Distance	24 Metres

#### REPLACEMENT PART

PART NUMBER	DESCRIPTION
BBOXWPL	LiFePO4 Lithium Battery, 3.2V 3200mAh

#### SPACING TABLE AND MOUNTING HEIGHT

CLASSIFICATION	2.1m	2.4m	2.7m	3m	3.3m	3.6m	4m	4.5m	5m
C2.5	4.5	4.6	4.6	4.5	4.4	0.0 <sup>4</sup>	0.0 <sup>4</sup>	0.0 <sup>4</sup>	N/A

