

# CODE: EXLEDLWP

## ALL-IN-ONE EASY CONNECT EXIT

- WITH WEATHERPROOF ENCLOSURE

### PRODUCT RANGE

PRODUCT CODE	DESCRIPTION
EXLEDLWP	3W LED All-in-One Easy Connect Exit with Weatherproof Enclosure

### ORDERING INFORMATION

Carton Qty	4 pieces
Weight	1.5kg (unit) - 6.0kg (box)
Dimension (L x W x H)	355mm x 80mm x 215mm



### OPERATIONAL INFORMATION

#### TECHNICAL SPECIFICATIONS

Operating Mode	Maintained
Voltage (V); Frequency (Hz)	220-260V; 50Hz
Operating Temperature	1° - 45° C
IP Rating	IP20
Wiring	Large Terminal Block
Mounting Type	Wall or Ceiling Surface Mount
Testing System	Manual Test Switch
Construction	Polycarbonate Body and Diffuser
Classification	C0 E2 C90 E2
Standards	AS/NZ 2293 AS/NZS 60598.1 EMC

#### BATTERY AND LEDS

Battery	High-Temp LiFePO4 Lithium Battery
Power Consumption	3W
Charging Method	3 Stage Intelligence
Charging Time	16 Hours
Lens	LED Lamp Rated 50,000 hours
Viewing Distance	24 Metres

#### REPLACEMENT PART

PART NUMBER	DESCRIPTION
BLEDL	LiFePO4 Lithium Battery, 3.2V 1600mAh

#### SPACING TABLE AND MOUNTING HEIGHT

CLASSIFICATION	2.1m	2.4m	2.7m	3m	3.3m	3.6m	4m	4.5m	5m
E2	5.0	5.2	5.2	5.2	0.0	0.0	0.0	0.0	N/A

