

PRODUCT RANGE

PRODUCT CODE	DESCRIPTION
EXWAY	All-in-One Economy Exit

ORDERING INFORMATION

Carton Qty	5 pieces
Weight	1.2kg (unit) - 6.0kg (box)
Dimension (L x W x H)	365mm x 80mm x 230mm



OPERATIONAL INFORMATION

TECHNICAL SPECIFICATIONS

Operating Mode	Switch Maintained
Voltage (V); Frequency (Hz)	220-260V; 50Hz
Operating Temperature	1° - 45° C
IP Rating	IP20
Wiring	Large Terminal Block
Mounting Type	Wall or Ceiling Surface Mount
Testing System	Manual Test Switch
Construction	Polycarbonate Body and Diffuser
Classification	C0 D8 C90 D6.3
Standards	AS/NZ 2293 AS/NZS 60598.1 EMC

BATTERY AND LEDS

Battery	High-Temp LiFePO4 Lithium Battery
Power Consumption	4W
Charging Method	3 Stage Intelligence
Charging Time	16 Hours
Lens	LED Lamp Rated 50,000 hours
Viewing Distance	24 Metres

REPLACEMENT PART

PART NUMBER	DESCRIPTION
BWAY	LiFePO4 Lithium Battery, 3.2V 1500mAh

SPACING TABLE AND MOUNTING HEIGHT

CLASSIFICATION	2.1m	2.4m	2.7m	3m	3.3m	3.6m	4m	4.5m	5m
D8	9.4	9.7	9.9	10.1	10.2	10.3	10.3	10.3	10.1
D6.3	8.5	8.8	8.9	9.1	9.1	9.2	9.1	9.0	8.7

