



E&E LIGHTING
AUSTRALIA

CODE: EXWAYBOX LED BOX EXIT BODY ONLY - WALL / CEILING DIFFUSER

PRODUCT RANGE

| CODE | DESCRIPTION | Carton Qty |
|----------|-----------------------------------|------------|
| EXWAYBOX | LED Box Exit Body Only | 6 pieces |
| DWAYBOXW | Wall Diffuser to suit EXWAYBOX | 6 pieces |
| DWAYBOXC | Ceiling Diffuser to suit EXWAYBOX | 4 pieces |

ORDERING INFORMATION

| PRODUCT | WEIGHT | DIMENSION (L X W X H) |
|------------------|----------------------------|-----------------------|
| Body Only | 0.9kg (unit) - 4.8kg (box) | 380mm x 65mm x 160mm |
| Wall Diffuser | 0.5kg (unit) - 3.0kg (box) | 380mm x 89mm x 160mm |
| Ceiling Diffuser | 1.0kg (unit) - 4.0kg (box) | 380mm x 160mm x 206mm |

LED Box Exit Body Only



Wall Diffuser



Ceiling Diffuser



OPERATIONAL INFORMATION

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------|---|
| Operating Mode | Switch Maintained |
| Voltage (V); Frequency (Hz) | 220-260V; 50Hz |
| Operating Temperature | 1° - 45° C |
| IP Rating | IP20 |
| Wiring | Large Terminal Block |
| Mounting Type | Wall or Ceiling Surface Mount |
| Testing System | Manual Test Switch |
| Construction | Polycarbonate Body and Diffuser |
| Classification | C0 D4 C90 D2.5 (Wall) C0 D8 C90 D6.3 (Ceiling) |
| Standards | AS/NZ 2293 AS/NZS 60598.1 EMC |

BATTERY AND LEDS

| | |
|-------------------|-----------------------------------|
| Battery | High-Temp LiFePO4 Lithium Battery |
| Power Consumption | 4W |
| Charging Method | 3 Stage Intelligence |
| Charging Time | 16 Hours |
| Lens | LED Lamp Rated 50,000 hours |
| Viewing Distance | 24 Metres |

REPLACEMENT PART

| PART NUMBER | DESCRIPTION |
|-------------|---------------------------------------|
| BWAYBOX | LiFePO4 Lithium Battery, 3.2V 1500mAh |

SPACING TABLE AND MOUNTING HEIGHT

| CLASSIFICATION | 2.1m | 2.4m | 2.7m | 3m | 3.3m | 3.6m | 4m | 4.5m | 5m |
|----------------|------|------|------|------|------|------|------|------|------|
| D4 | 7.1 | 7.2 | 7.3 | 7.3 | 7.2 | 7.1 | 6.9 | 0.0 | 0.0 |
| D8 | 9.4 | 9.7 | 9.9 | 10.1 | 10.2 | 10.3 | 10.3 | 10.3 | 10.1 |
| D2.5 | 5.8 | 5.8 | 5.7 | 5.6 | 5.3 | 0.0 | 0.0 | 0.0 | 0.0 |
| D6.3 | 8.5 | 8.8 | 8.9 | 9.1 | 9.1 | 9.2 | 9.1 | 9.0 | 8.7 |



0487 248 481



sales@eelighting.com.au



eelighting.com.au